

adaptateur de jeu de barres 160 A, à 3 pôles (32068)



The picture may show a similar product.

Description

Référence **32068 000A**

EQUES® 60Classic

adaptateur de jeu de barres 160 A, à 3 pôles

90 x 200

raccordement à l'adaptateur par le haut

pour Schneider Electric NSXm160, NG125, PowerPact B125

pour jeux de barres 12, 15, 20, 25, 30 x 5, 10 et barres profilées

Système

60Classic

Groupe de produits 05

Sous-groupe 30

Dimensions de l'emballage 1

EAN 4021267320683

ECLASS 6.1 27370304
ECLASS 7.1 27370304
ETIM 4.0 EC001531
ETIM 5.0 EC001531

Homologations

Normes

IEC 61439-1:2020
UL 508

Approbations

CSA , UL



for UL feeder circuits >250V

Type: EPC60160-L

UL file: E123577, UL category (for USA): NMTR <https://www.ul.com>
UL file: E123577, UL category (for Canada): NMTR7 <https://www.ul.com>
CSA file: 110285, CSA class: 3211-37 <https://directories.csa-international.org>
Homologation CCC: no certification required

Données techniques

Details IEC

Normes

IEC 61439-1:2020

Electrical data IEC

Courant assigné (IEC): 160 A
Tension assignée (IEC) CA: 690 V

rated isolation voltage U_i AC: 800 V
Tension assignée de tenue aux chocs U_{imp} : 6 kV

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 7,7 W.

(The power dissipation at full load would be 12,0 W.)

Details UL

Normes

UL 508

for UL feeder circuits >250V

Electrical data UL

rated current (UL): 125 A

rated voltage (UL) AC: 600 V

rated frequency (UL): 50 / 60 Hz

SCCR protected max.: 65 kA

with any DIVQ/7 125 A / 480 V AC

Caractéristiques mécaniques

L x H x P: 90 x 200 x 66

Poids: 81,0 kg/100

Pôles: 3 pôles

pour jeux de barres: 12, 15, 20, 25, 30 x 5, 10 et barres profilées

Application notes

There must be a clearance of at least 10 mm above the article to remove it from the busbar system.

the short-circuit capacity of the combination of adapter and MCCB depends on the MCCB

for UL feeder circuits >250V

<https://pim.woehner.de/FR/FR/1000230360>