

2900 Pg

MAXIBRASS CABLE GLAND, IN NICKEL-PLATED BRASS, PG PITCH, IP68



CERTIFICATIONS & APPROVALS

CE

CE

UK

CA

UKCA

UL

US

UL (cURus)

UL

US

UL (cULus)

Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Range of operating temperature (static)	-40 ÷ 100 °C
External seal	Yes
Colour	Nickel plated brass grey
Surface treatment	nickel plating

CLASSIFICATION AND DATA ORDERING


Customs code	74198090
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	brass
Inner seal material	Neoprene
Outer seal material	Nitrile 70 sh A
Body material	brass
Cage material	Polyamide PA6.6

CERTIFICATIONS

ROHS compliant	Yes
UL standard	514B
EN ISO 4892-2	Yes



2900 PG

tipo	P	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width	Unit in minimal packaging [pce]	Unit in standard packaging [pce]
2900.07N	Pg7	6.25	3 ÷ 7	16	16	5	16 ÷ 20	12.7	18	100	100
2900.09N	Pg9	6.25	4 ÷ 8	17	17	6	17 ÷ 23	15.5	19	100	100
2900.11N	Pg11	6.25	4.5 ÷ 11	20	20	6	20 ÷ 25	18.8	22.5	100	100
2900.13N	Pg13.5	7.5	5 ÷ 12	22	22	6.5	20 ÷ 26	20.5	24.5	50	50
2900.16N	Pg16	7.5	7 ÷ 13	24	24	6.5	20 ÷ 27	22.6	27	50	50
2900.21N	Pg21	10	10 ÷ 17	30	30	7	24 ÷ 30	28.5	33.3	50	50
2900.29N	Pg29	15	17 ÷ 25	40	40	8	30 ÷ 37	37.2	43.5	25	25
2900.36N	Pg36	25	20 ÷ 32	50	50	8	38 ÷ 48	47.2	54	10	10
2900.42N	Pg42	25	28 ÷ 38	57	57	10	39 ÷ 48	54.2	61	5	5
2900.48N	Pg48	25	34 ÷ 45	67	67	15	40 ÷ 52	60	73.5	5	5