

2900 M

MAXIBRASS CABLE GLAND, IN NICKEL-PLATED BRASS, METRIC PITCH, IP68



CERTIFICATIONS & APPROVALS

 CE

 UKCA

 UKCA

 ULUS

 UL (cURus)

 D'E

 VDE

 ULUS

 UL (cULus)

Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Range of operating temperature (static)	-40 ÷ 100 °C
External seal	Yes
Colour	Nickel plated brass grey
Surface treatment	nickel plating

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	brass
Inner seal material	Neoprene
Outer seal material	Nitrile 70 sh A
Body material	brass
Cage material	Polyamide PA6.6

CLASSIFICATION AND DATA ORDERING

Customs code	74198090
--------------	----------

CERTIFICATIONS

Compliance according to CEI EN 62444	Yes
--------------------------------------	-----

2900 M

tipo	P	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL impact rating	UL standard	EN ISO 4892-2
2900.M12N	M12x1.5	6	3 ÷ 7	16	16	6.5	16 ÷ 20	12.2	18	100	100	Yes	5	514B	Yes
2900.M16N	M16x1.5	6	4.5 ÷ 10	20	20	7	20 ÷ 25	16.2	22.5	100	100	Yes	6	514B	Yes
2900.M20N	M20x1.5	8	7 ÷ 13	24	24	8	20 ÷ 27	20.5	27	50	50	Yes	6	514B	Yes
2900.M25N	M25x1.5	8	10 ÷ 17	29	29	8	24 ÷ 30	25.4	32	50	50	Yes	6	514B	Yes
2900.M32N	M32x1.5	18	11 ÷ 21	36	36	9	27 ÷ 34	32.5	39	25	25	Yes	6	514B	Yes
2900.M40N	M40x1.5	18	19 ÷ 28	45	45	9	34 ÷ 42	40.5	50	10	10	Yes	6	514B	Yes
2900.M50N	M50x1.5	18	26 ÷ 35	54	54	10	35 ÷ 43	50.5	59.5	8	8	Yes	6	514B	Yes
2900.M63N	M63x1.5	25	34 ÷ 45	67	67	15	40 ÷ 52	64	73.5	5	5	Yes	6	514B	Yes
2900.M75N	M75x1.5	40	56 ÷ 63	80	80	18	35 ÷ 43	76	88	1	3		6		



