

7900 M

MAXIINOX CABLE GLAND, IN AISI 303 STAINLESS STEEL, METRIC PITCH, IP68



CERTIFICATIONS & APPROVALS

 CE

 UKCA

Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Range of operating temperature (static)	-40 ÷ 100 °C
External seal	Yes
Colour	Steel

CLASSIFICATION AND DATA ORDERING


Customs code	73269098
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	stainless steel AISI 303
Inner seal material	Neoprene
Outer seal material	Nitrile 70 sh A
Body material	stainless steel AISI 303
Cage material	Polyamide PA6.6

CERTIFICATIONS

ROHS compliant	Yes
Ingress Protection	IP68



7900 M

tipo	P	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width	Unit in minimal packaging [pce]	Unit in standard packaging [pce]
7900.M12	M12x1.5	6	3 ÷ 7	16	16	6.5	16 ÷ 20	12.2	18	30	90
7900.M16	M16x1.5	6	4.5 ÷ 10	20	20	7	20 ÷ 25	16.2	22.5	30	120
7900.M20	M20x1.5	8	7 ÷ 13	24	24	8	20 ÷ 27	20.5	27	25	75
7900.M25	M25x1.5	8	10 ÷ 17	29	29	8	24 ÷ 30	25.4	32	20	40
7900.M32	M32x1.5	18	11 ÷ 21	36	36	9	27 ÷ 34	32.5	40	15	15
7900.M40	M40x1.5	18	19 ÷ 28	45	45	9	34 ÷ 42	40.5	50	15	15
7900.M50	M50x1.5	18	26 ÷ 35	54	54	10	35 ÷ 43	50.5	59.5	10	10
7900.M63	M63x1.5	25	34 ÷ 45	67	67	15	40 ÷ 52	64	73.5	5	5