

20M3

EMC CABLE GLAND, IN NICKLE-PLATED BRASS, METRIC PITCH, IP68.5



CERTIFICATIONS & APPROVALS

CE

UKCA

UKCA

UL

UL (cURus)

Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Range of operating temperature (static)	-40 ÷ 100 °C
External seal	Yes
Colour	Nickel plated brass grey
Surface treatment	nickel plating

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	brass
Inner seal material	Chloroprene
Outer seal material	NBR
Body material	brass
Cage material	Polyamide PA6.6

CLASSIFICATION AND DATA ORDERING

Customs code	74198090
--------------	----------

CERTIFICATIONS

ROHS compliant	Yes
Ingress Protection	IP68

20M3

tipo	P	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]
20M3M1261N	M12x1.5		3 ÷ 6.5	14	14	5	22	12.2	100	300
20M3M1661N	M16x1.5		5.5 ÷ 10	17	17	5.5	24.5	16.2	100	200
20M3M2061N	M20x1.5	8	8 ÷ 13	22	22	6	27	20.5	50	100
20M3M2561N	M25x1.5		11 ÷ 18	30	30	7	31	25.4	25	50
20M3M3261N	M32x1.5		15 ÷ 21	34	34	8	33	32.5	10	30
20M3M4061N	M40x1.5		19 ÷ 27	44	44	8	40	40.5	10	20
20M3M5061N	M50x1.5		26 ÷ 35	55	55	9	48	50.5	5	10
20M3M6361N	M63x1.5		39 ÷ 48	66	66	10	50	64	5	5