

module PE/N (32146)



The picture may show a similar product.

Description

Référence **32146** 000

module PE/N

encliquetable dans l'Adaptateur pour jeu de barres des deux côtés

18 x 242

pour jeux de barres 12, 15, 20, 25, 30 x 5, 10 et barres profilées

Système

60Classic

Groupe de produits 05

Sous-groupe 43

Dimensions de l'emballage 4

EAN 4021267321468

ECLASS 6.1 27370304

ECLASS 7.1 27370304

ETIM 4.0 EC001531

ETIM 5.0 EC001531

Homologations

Normes

IEC 61439-1:2020

UL 508

Approbations

UL



Type: 680.1

UL file: E123577, UL category (for USA): NMTR2 <https://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <https://www.ul.com>

Homologation CCC: no certification required

Données techniques

Details IEC

Normes

IEC 61439-1:2020

Electrical data IEC

Tension assignée (IEC) CA: 690 V

rated isolation voltage U_i AC: 690 V

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0,9 W.

(The power dissipation at full load would be 1,4 W.)

Connecting terminals 16 mm² top and bottom

Details UL

Normes

UL 508

Caractéristiques mécaniques

L x H x P: 18 x 242 x 50

Poids: 14,1 kg/100

Pôles: 3 pôles + N

pour jeux de barres: 12, 15, 20, 25, 30 x 5, 10 et barres profilées

Torque for busbar contacting 12Nm

Torque for pipe connection 40Nm

Application notes

There must be a clearance of at least 12 mm above the article to remove it from the busbar system.

For feeding and tapping the PE/N busbar

version is without connection leads

assembly on the 60mm-System only possible in conjunction with an adapter or device carrier

both sides can be plugged onto all adapters, device carriers and side-mounted modules.

<https://pim.woehner.de/FR/FR/1000043394>