

7900A Pg
MAXIINOX CABLE GLAND, IN AISI 316L STAINLESS STEEL, PG PITCH, IP68



CERTIFICATIONS & APPROVALS

CE CE UK UKCA UKCA

Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Range of operating temperature (static)	-40 ÷ 100 °C
External seal	Yes
Colour	Steel

CLASSIFICATION AND DATA ORDERING

Customs code	73269098
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	stainless steel AISI 316L
Inner seal material	Neoprene
Body material	stainless steel AISI 316L
Cage material	Polyamide PA6.6

CERTIFICATIONS

ROHS compliant	Yes
Ingress Protection	IP68

7900A PG

tipo	P	Outer seal material	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width	Unit in minimal packaging [pce]	Unit in standard packaging [pce]
7900A.07	Pg7	Nitrile 70 sh A	6.25	3 ÷ 7	16	16	5	16 ÷ 20	12.7	18	20	60
7900A.09	Pg9	Nitrile 70 sh A	6.25	4 ÷ 8	17	17	6	17 ÷ 23	15.5	19	20	60
7900A.11	Pg11	Nitrile 70 sh A	6.25	4.5 ÷ 11	20	20	6	20 ÷ 25	18.8	22.5	20	100
7900A.13	Pg13.5	Nitrile 70 sh A	7.5	5 ÷ 12	22	22	6.5	20 ÷ 26	20.5	24.5	20	100
7900A.16	Pg16	Nitrile 70 sh A	7.5	7 ÷ 13	24	24	6.5	20 ÷ 27	22.6	27	20	40
7900A.21	Pg21	Nitrile 80 sh A	10	10 ÷ 17	30	30	7	24 ÷ 30	28.5	33.3	15	60
7900A.29	Pg29	Nitrile 70 sh A	15	17 ÷ 25	40	40	8	30 ÷ 37	37.2	44.5	10	20
7900A.36	Pg36	Nitrile 70 sh A	25	20 ÷ 32	50	50	8	38 ÷ 48	47.2	55	7	7
7900A.42	Pg42	Nitrile 70 sh A	25	28 ÷ 38	57	57	10	36 ÷ 46	54.2	63	5	5
7900A.48	Pg48	Nitrile 70 sh A	25	34 ÷ 45	67	67	15	40 ÷ 52	60	73.5	5	5

