

transformateur de courant 150 A / 5 A (33751)



The picture may show a similar product.

Description

Référence **33751 000**

transformateur de courant 150 A / 5 A

Size CT3

2,5 VA / classe 0,5

taille 00

Système

185Power

Groupe de produits 23

Sous-groupe 01

Dimensions de l'emballage 1

EAN 4021267337513

ECLASS 6.1 27210902

ECLASS 7.1 27210902

ETIM 4.0 EC002048

ETIM 5.0 EC002048

Homologations

Normes

IEC 61869-1:2007

IEC 61869-2:2012

Homologation CCC: no certification required

Données techniques

Taille: CT3

Details IEC

Normes

IEC 61869-1:2007

IEC 61869-2:2012

Electrical data IEC

prim. rated current I_{pr} :	150 A
sec. rated current:	5 A
sec. rated apparent power:	2.5 VA
accuracy class (current):	0.5
max. operation voltage U_M :	720 V
therm. short-time current I_{th} :	9 kA
class of insulation:	E

over-current limitation factor: FS5

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 3,2 W.

(The power dissipation at full load would be 5,0 W.)

Caractéristiques mécaniques

L x H x P: 44 x 30 x 66

Poids: 28,0 kg/100

CT can be integrated in the device: ja
CT can be integrated in the CT module: nein

sealable: nein

Points de raccordement

double terminal

min. cross-section: 2,5 mm²

max. cross-section: 4 mm²

Not suitable for aluminium cables !

Application notes

Not suitable for aluminium cables !

<https://pim.woehner.de/FR/DE/1000155909>