

7900 Pg

MAXIINOX CABLE GLAND, IN AISI 303 STAINLESS STEEL, PG PITCH, IP68



CERTIFICATIONS & APPROVALS



Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Range of operating temperature (static)	-40 ÷ 100 °C
External seal	Yes
Colour	Steel

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	stainless steel AISI 303
Inner seal material	Neoprene
Outer seal material	Nitrile 70 sh A
Body material	stainless steel AISI 303
Cage material	Polyamide PA6.6

CLASSIFICATION AND DATA ORDERING

Customs code	73269098
--------------	----------

CERTIFICATIONS

ROHS compliant	Yes
Ingress Protection	IP68

7900 PG

tipo	P	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width	Unit in minimal packaging [pce]	Unit in standard packaging [pce]
7900.07	Pg7	6.25	3 ÷ 7	16	16	5	16 ÷ 20	12.7	18	30	90
7900.09	Pg9	6.25	4 ÷ 8	17	17	6	17 ÷ 23	15.5	19	30	90
7900.11	Pg11	6.25	4.5 ÷ 11	20	20	6	20 ÷ 25	18.8	22.5	30	60
7900.13	Pg13.5	7.5	5 ÷ 12	22	22	6.5	20 ÷ 26	20.5	24.5	30	90
7900.16	Pg16	7.5	7 ÷ 13	24	24	6.5	20 ÷ 27	22.6	27	30	60
7900.21	Pg21	10	10 ÷ 17	30	30	7	24 ÷ 30	28.5	33.3	20	40
7900.29	Pg29	15	17 ÷ 25	40	40	8	30 ÷ 37	37.2	44.5	15	30
7900.36	Pg36	25	20 ÷ 32	50	50	8	38 ÷ 48	47.2	55	10	10
7900.42	Pg42	25	28 ÷ 28	57	57	10	36 ÷ 46	54.2	63	5	5
7900.48	Pg48	25	34 ÷ 45	67	67	15	40 ÷ 52	60	73.5	5	5



