

2940 M

MAXIBRASS CABLE GLAND, IN NICKEL-PLATED BRASS, WITH EXTENDED CLAMPING RANGE, METRIC PITCH, IP68



CERTIFICATIONS & APPROVALS



Features

TECHNICAL INFORMATION

Range of operating temperature (dynamic)	-25 ÷ 100 °C
Range of operating temperature (static)	-40 ÷ 100 °C
External seal	Yes
Colour	Nickel plated brass grey
Surface treatment	nickel plating

CLASSIFICATION AND DATA ORDERING


Customs code 74198090

MATERIAL COMPOSITION AND TREATMENTS

Entry bush material	brass
Inner seal material	Neoprene
Outer seal material	Nitrile 70 sh A
Body material	brass
Cage material	Polyamide PA6.6

CERTIFICATIONS

Compliance according to CEI EN 62444	Yes
--------------------------------------	-----



2940 M

tipo	P	Tightening torque [nm]	Range of cable housing diameter [mm]	B1 [mm]	B2 [mm]	C [mm]	L [mm]	Fixing hole diameter [mm]	Width	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	UL impact rating	UL standard
2940.M12N	M12x1.5	6	5 ÷ 8	17	17	6.5	17 ÷ 23	12.2	19	100	100	5	514B
2940.M16N	M16x1.5	6	7 ÷ 12	22	22	7	20 ÷ 26	16.2	24.5	50	50	6	514B
2940.M20N	M20x1.5	8	10 ÷ 16	29	29	10	24 ÷ 30	20.5	32	50	50	6	514B
2940.M25N	M25x1.5	8	13 ÷ 21	36	36	11	27 ÷ 34	25.4	39	25	25	6	514B
2940.M32N	M32x1.5	18	18 ÷ 25	40	40	12	30 ÷ 37	32.5	43.5	25	25	6	514B
2940.M40N	M40x1.5	18	25 ÷ 32	50	50	13	38 ÷ 48	40.5	54	10	10	6	514B
2940.M50N	M50x1.5	18	30 ÷ 38	57	57	13	39 ÷ 48	50.5	61	5	5	6	514B
2940E.M50N	M50x1.5	18	35 ÷ 45	67	67	13	40 ÷ 52	50.5	73.5	5	5	6	514B
2940.M63N	M63x1.5	25	44 ÷ 55	75	75	15	40 ÷ 53	64	83	4	4	6	