

adaptateur de jeu de barres 32 A (32428)



The picture may show a similar product.

Description

Référence **32428 000**

EQUES® 60Classic

adaptateur de jeu de barres 32 A

3 pôles

pour démarreur direct Schneider Electric LUB12, LUB32

45 x 260, avec câbles AWG 10 (6 mm²)

pour jeux de barres 12, 15, 20, 25, 30 x 5, 10 et barres profilées

Système

60Classic

Avantages produit

Conductor ends ultrasonically sealed.

Click mechanism when pushing onto the busbar.

Groupe de produits 05

Sous-groupe 21

Dimensions de l'emballage 4
EAN 4021267324285

ECLASS 6.1 27370304
ECLASS 7.1 27370304
ETIM 4.0 EC001531
ETIM 5.0 EC001531

Homologations

Normes

IEC 61439-1:2020
UL 508

Approbations

CSA , UL



for UL feeder circuits >250V

Type: EEC6025-L

UL file: E123577, UL category (for USA): NMTR <https://www.ul.com>
UL file: E123577, UL category (for Canada): NMTR7 <https://www.ul.com>
CSA file: 110285, CSA class: 3211-37 <https://directories.csa-international.org>
Homologation CCC: no certification required

Données techniques

Details IEC

Normes

IEC 61439-1:2020

Electrical data IEC

Courant assigné (IEC): 32 A
Tension assignée (IEC) CA: 690 V

rated isolation voltage U_i AC: 800 V
Tension assignée de tenue aux chocs U_{imp} : 6 kV

power dissipation of the article:
The power dissipation at a typical load of 80 % results to 1,6 W.
(The power dissipation at full load would be 2,5 W.)

Details UL

Normes

UL 508

for UL feeder circuits >250V

Electrical data UL

rated current (UL): 32 A
rated voltage (UL) AC: 600 V
rated frequency (UL): 50 / 60 Hz

SCCR unprotected max.: 5 kA
3 cycles (without OPD) @ 600 V AC
SCCR protected max.: 65 kA

SCCR: 65 kA with LUB32 25 A / 480 V AC
50 kA with LUB32 32 A / 480 V AC
30 kA with LUB12, LUB32 12,5 A / 600 V AC

Caractéristiques mécaniques

L x H x P: 45 x 260 x 63
Poids: 35,1 kg/100
Pôles: 3 pôles
pour jeux de barres: 12, 15, 20, 25, 30 x 5, 10 et barres profilées

Points de raccordement

with leads
AWG10 (6 mm²)
wire stripping: 9 mm


Application notes

There must be a clearance of at least 12 mm above the article to remove it from the busbar system.
the short-circuit capacity of the combination of adapter and motor starter depends on the motor starter

for UL feeder circuits >250V

Accessoires

further accessories



32963 000

module pour montage latéral pour adaptateurs de jeu de barres
encliquetable des deux côtés

9 x 200

pour: EEC60..

<https://pim.woehner.de/FR/FR/1000042678>